



## All Noise Control ANC-700 Baffles Specification

### Part I: General

#### 1.1 Work Included:

The work consists of furnishing all labor, materials, accessories and equipment necessary to cover all areas shown on the drawings and specified herein with ANC Panels.

#### 1.2 Delivery and Storage:

Store this product in unopened cartons in a clean, cool, dry interior space. Cartons and product must be protected against marring, water, dirt or damage during delivery and storage.

### Part II: Product

2.1.1 Geometric Shape: rectangular

2.1.2 Size & Thickness: \_\_\_\_\_  
(2" thick) (4' x 2')

2.1.3 Core: 3/4# fiberglass

2.1.4 Surface Finish: \_\_\_\_\_  
(PVC perforated one side) (nylon sailcloth perforated one side) (also available solid both sides for high humidity environments)

2.1.5 Color: To be selected by architect from manufacturer's standard selection

2.1.6 Edge Shape: natural

2.1.7 Edge Construction: \_\_\_\_\_  
(heat sealed)

2.1.8 Acoustical Performance:  
1.0 N.R.C.

2.1.9 Incombustibility: Class "A"

2.1.10 Suspension Provision: \_\_\_\_\_  
(grommets)

### Part III: Execution

#### 3.1 Installation

3.1.1 ANC acoustical panels shall be located and spaced as detailed on reflected ceiling plans and/or detailed on the interior elevation drawings and as indicated on room finish schedule.

3.1.2 Suspend Panels From: \_\_\_\_\_  
(existing construction) (cable)  
(fasteners [type])

3.1.3 Attachment Method: \_\_\_\_\_  
(heavy duty plastic tie) (coated wire tie)  
(beam clamps) (cable)

#### 3.1.4 Workmanship

The acoustical system shall be installed only by an approved contractor.

All work shall be completed in a workman like manner. All panels shall be properly installed and left in a clean, sanitary condition. Contractor shall remove and dispose of shipping containers and debris.